

DIVISION OF INDUSTRY SERVICES PO BOX 7162 MADISON WI 53707-7162 Contact Through Relay http://dsps.wi.gov/programs/industry-services www.wisconsin.gov

> Scott Walker, Governor Dave Ross, Secretary

Identification Numbers

Transaction ID No. 2657427 Site ID No.

Please refer to both identification numbers, above, in all correspondence with the agency.

January 25, 2016

CUST ID No. 1315288

DAVID URBAN MCC INC N7820 OLD HWY 141 CRIVITZ WI 54114

PLAN APPROVAL EXPIRES: 01/30/2021

Re: Description: SEWAGE TANKS, CONCRETE

Manufacturer: MCC INCORPORATED

Product Name: SEPTIC/SEPTIC, SEPTIC/PUMP, HOLDING OR PUMP (trans id 2657427)

Model Number(s): 1200/800 (804/1260 gals. actual capacity)

(49.5 IN. L.L., 25.5/16.3 GAL/IN., 48 IN. MAX. DEPTH OF BURY, 991 G.P.D. WHEN USED AS A SEPTIC/SEPTIC TANK OR 605 G.P.D. WHEN USED AS A

SEPTIC/PUMP TANK BASED ON A 3 YR. SERVICE INTERVAL FOR

RESIDENTIAL WASTEWATER; TANK DIMENSIONS (OD) = 145 IN. L X 78 IN.

W X 66.5 IN. H)

Product File No: 20160009

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters SPS 382 through 384, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. **This approval is valid until the end of January 2021.**

This approval supersedes the approval issued on 5/3/2011 under product file number 20110156.

This approval is contingent upon compliance with the following stipulation(s):

- This product is approved to use the following:
 - 3/4" diameter opening in the access riser.
 - Department approved effluent filter installed in accordance with the product approval for the filter including a properly sized and located access opening for service and maintenance.
- This tank must be designed to withstand the pressures to which it will be subjected.
- The manufacturer must keep at the manufacturing plant a set of plans and specifications bearing the department's stamp of approval. The plans and specifications must be open to inspection by an authorized representative of the department.
- When this product has an effluent filter installed in an interior wall, the space between the top of the interior wall and bottom of the tank's cover must be sealed with a material that will withstand the environment in the tank and in a manner that will prevent waste from passing over the interior wall.

2657427 DAVID URBAN Page 2 1/25/2016

When this product receives wastewater from dwellings and is used as a septic tank, it will produce an
effluent quality with a maximum monthly average value for BOD5 greater than 30 mg/L but less than
or equal to 220 mg/L, TSS greater than 30 mg/L but less than or equal to 150 mg/L and F.O.G. less
than or equal to 30 mg/L.

• BEDDING AND BACKFILL: Tank bedding must be 3 in. of compacted sand, gravel or lime rock of which 100% will pass through ½-inch screen. Backfill material must be material that 100% will pass through a 4-inch screen and tamped into place.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation which may result from its use.

Sincerely,

Glen Jones, M.S. POWTS Product Reviewer phone: (608) 267-5265 fax: (608) 267-9723 email: glen.jones@wi.gov

The DSPS is committed to service excellence. Visit our survey at:

www.surveymonkey.com/s/dspsiscustomersatisfaction